TITLE TO REAL ESTATE	
THE STATE OF SOUTH CAROLINA,	On Table
County of Greenville	
KNOW ALL MEN BY THESE PRESENTS, That I, Mrs. Rudie B. Gradick	II.
	in the State aforesaid,
Two Hundred (\$200.00)	, Dollars
•	l l
, to	
at and before the sealing of these presents by	
Troy A. Taylor	
	Li .
(the receipt whereof is hereby acknowledged) have granted, bargained, sold, and released, and by these presents do grant, bargain,	sell and release unto the said
Troy A. Taylor	
All that piece, parcel or lot of land in Greenville Greenville	County, State of South Carolina.
A portion of that lot of land in the above state and County located about two	o_and_one=nall_mlles t side of Perry Road.
north of the City of Greenville, in the Sans Souci section, lying on the eas and is a part of lot number 7 as shown on Plat made by A. S. Bedell revised	by C. M. Furman, Jr.,
and is a part of lot number 7 as shown on list made by as sonveyed to this recorded in Plat Book "C" at page 158. The whole lot was conveyed to this	Grantor by Traxler
Real Estate Company by deed dated June 11, 1920, recorded in Deed Book "80"	at page 2. The
portion of said lot herein conveyed consists of the rear end of the lot above	e mentioned and is
described_as_follows:	
	od 81 feet from the
Beginning at an iron pin in the southern line of said lot which pin is locat	eu_01_1000_110m_024
thomas 5 74-26 F. 81 feet to the rear C	orner of the original
neen company and running said line thence. S. 74-26 E. 81 feet to the rear c	orner_or_the_original
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E.	for a distance of ce, running the
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner, and running said line thence, running the rear line of the lot 33-51 E.	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight
rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner, and running said line thence, S. 74-26 E. 81 feet to the rear corner of the lot 33-51 E. 59.25 feet to an iron pin marking the northern rear corner of said lot; then northern line of the lot N. 74-26 W. 99 feet to an iron pin; thence, running	for a distance of ce, running the a line straight